

## ConfyC - configuration file grammar

```
<configfile>           = <section>
<section>              = <section_declaration> <insection>
<section>              = empty
<insection>           = <section>
<section_declaration> = <section_header> <section_body> <section_footer>
<section_header>      = <sh_lead_chars> <sh_keyword> <sh_ident> <optional_flags>
                       <sh_follow_chars>
<section_header>      = empty
<section_footer>      = <sf_lead_chars> <optional_footer_statement>
                       <sf_follow_chars>
<section_footer>      = empty
<section_body>        = <configuration_line> <section_body>
<section_body>        = empty
<sh_lead_chars>       = ide
<sh_lead_chars>       = empty
<sh_follow_chars>     = ide
<sh_follow_chars>     = empty
<sf_lead_chars>       = ide
<sf_lead_chars>       = empty
<sf_follow_chars>     = ide
<sf_follow_chars>     = empty
<sh_keyword>          = ide
<sh_ident>            = ide
<sh_ident>            = empty
<optional_flags>      = <flag> <optional_flags>
<optional_flags>      = empty
<flag>                = ide
<optional_footer_statement> = ide
<configuration_line> = <optional_leading_char> <option> <optional_closing_char>
<optional_leading_char> = ide
<optional_leading_char> = empty
<optional_closing_char> = ide
<optional_closing_char> = empty
<option>              = <op_name> <optional_connector> <op_list>
<op_name>             = ide
<optional_connector> = ide
<optional_connector> = empty
<op_list>             = <op_flag> <op_list_cont>
<op_flag>             = ide
<op_flag>             = <option>
<op_flag>             = number
<op_flag>             = empty
<op_list_cont>        = <optional_divide> <op_flag> <op_list_cont>
<op_list_cont>        = empty
<optional_divide>     = ide
<optional_divide>     = empty
ide                   = keyword
ide                   = string
```